Model AC-15EX

Model AC-11H

Non-Contact detection of AC Voltage

The Non-contact AC Voltage Testers are easy to use — just touch the tip to a terminal strip, outlet, or supply cord. When the tip glows red and the unit beeps, you know there's voltage present. Electricians, maintenance, service, safety personnel, and homeowners can quickly test for energized circuits in the workplace or at home.

- High power rear flashlight
- Thinner probe tip for working with wall outlets
- Green LED means power on, flashing red LED with beeper means voltage detected
- Low battery selftest & Auto power off
- Two modes, green means high voltage mode, yellow means low voltage mode
- Forward facing flashlight
- Flash and Beep rate increase as the detector gets closer to the voltage source helping the user pinpoint live circuits

 • Power ON/OFF swith & Silent Mode
- Pocket clip for easy storage
- CATIV-1000V, IP67 Water proof & 2m drop-proof
- ATEX certificate for AC-15Ex/AC-15Exs
 - High power rear flashlight • Dual Voltage Sensitivity detector
- IP67 Water proof & 2m drop-proof







| Specificati | ons | | | | | | | | | |
|----------------------------------|-------------------------------------------------|---------------|--------|--------|-------|--------|--------|---------|----------|--|
| _ | | AC-11 | AC-11B | AC-11H | AC-15 | AC-15B | AC-15S | AC-15Ex | AC-15 Ex | |
| ACV Non-Contact Detection | | * | * | * | * | * | * | * | * | |
| Operating Range (50Hz/60Hz) | 12V to1000V | * | | * | * | | | * | | |
| | 24V to1000V | | * | | | * | | | | |
| | 50V to1000V | | | | | | * | | * | |
| | 100V to 1000V | * | * | | * | * | | * | | |
| | 200V to 1000V | | | * | | | * | | * | |
| IP67 Water proof & 2m drop-proof | | 2m drop-proof | | * | * | * | * | * | * | |
| Motor shaking | | | | | | | * | | * | |
| Ex ib IIB T4 (ATEX) | | | | | | | | * | * | |
| Dual Voltage Sens | sitivity detector | | | | | | | | | |
| Red/Yellow/Green | n LED indicators | | | | | | | | | |
| Flashlight function | n | | | | | | | | | |
| Auto Power Off | | | | | | | | | | |
| Beeper sounds | | | | | | | | | | |
| System self test | | | | | | | | | | |
| Switchable audible | and silent mode | | | | | | | | | |
| Rugged, double m | nolded case | | | | | | | | | |
| CATIV-1000V | | | | | | | | | | |
| Size(HxWxD) | 160 x 20 x 23mm 155x26x23mm 160mm x 23mm x 25mm | | | | | | | | | |
| Weight | | 6 | 50g | 55g | 55g | | | | | |

Accessories: Two "AAA" batteries and clamshell











- Easy-to-use just touch the tip to an outlet or cord. When it glows red, you know there is voltage in the line.
- Fit in shirt pocket for convenience
- All outer surfaces are non-conductive for safety
- Detects AC voltage without metallic contact



| Features | | | | | | | | | | | | | |
|---------------------------------------|---------------|---------------|-------|-------|--------|---------------|-------|---------------|------|-------|---------------|-------|--------|
| | | AC-6 | AC-6B | AC-6S | AC-6H | AC-8 | AC-8B | AC-8S | AC-9 | AC-9B | AC-9C | AC-10 | AC-10S |
| ACV Non-Contact Detection | | * | * | * | * | * | * | * | * | * | * | * | * |
| Operating Range (50Hz/60Hz) | 24V to1000V | | | * | | | | * | | | | | |
| | 50V to1000V | * | | | 12V to | * | | | | | | | * |
| | 100V to 1000V | | * | * | 1000V | | * | * | * | * | | | |
| | 200V to 1000V | | | | | | | | * | * | * | * | |
| Voltage Sensitivity detector (Single) | | * | * | Dual | Dual | * | * | Dual | * | * | * | * | * |
| Red LED indicators | | * | * | * | * | * | * | * | * | * | * | * | * |
| Yellow LED indicators | | | | * | * | | | * | | | | | |
| Green LED indicators | | * | * | * | * | * | * | * | | | | * | * |
| Beeper sounds | | * | * | * | * | | * | * | | * | | * | * |
| Motor Shaking | | | | | | | | | | | * | | |
| Flashlight function | | AC-6F | | | | * | * | * | * | * | * | * | * |
| Auto Power Off | | * | * | * | * | * | * | * | * | * | * | * | * |
| Low battery self test | | * | * | * | * | * | * | * | | | | * | * |
| Power ON/OFF switch | | * | * | * | * | * | * | * | | | | * | * |
| Switchable audible and silent mode | | * | * | * | * | | | | | | | * | * |
| Rugged, double molded case | | * | * | * | * | * | * | * | * | * | * | * | * |
| CATIII-1000V | | * | * | * | * | * | * | * | * | * | * | * | * |
| Size(HxWxD) mm | | 135 x 19 x 22 | | | | 158 x 21 x 25 | | 176 x 22 x 26 | | | 135 x 19 x 22 | | |
| Weight | | 45g | | | | 48g | | | 50g | | | 55g | |

