All models with Near Field Communication Technology Bluetooth available as an option

Digital Hand-Held "Pocket" Refractometer PAL Special Scales

					•			
Cat.No.	Model	Scale	Cat.No.	Model	Scale	Cat.No.	Model	Scale
Food, Co	onfectionery,	Food Ingredients	4404	PAL-04S	Sodium chloride (S.G.)	4491	PAL-91S	Ethylene glycol Freezing point of
4422	PAL-22S	Honey moisture	4405	PAL-05S	Sodium chloride (Baume)			Ethylene glycol (°C)
4508	PAL-Pâtissier	Brix / Baume (Dual scale)	4406	PAL-06S	Seawater (Concentration)	4492	PAL-92S	Ethylene glycol Freezing point of
3807	PAL-MILK	Non-fat milk solids	4407	PAL-07S	Seawater (S.G.)	Pofracti	ve Index • Bri	Ethylene glycol (°F)
4427	PAL-27S	Soymilk	4408	PAL-08S	Seawater (Baume)	3852	PAL-BX/RI	Brix / Refractive Index
1443	PAL-43S	Bittern (Magnesium chloride)	Moistur	e		3850	PAL-RI	Refractive Index
1496	PAL-96S	Chinese noodle soup / Baume of	4573	PAL-Moisture	Moisture	3840	PAL-NI	Brix
		Kansui (Dual scale)	4574	PAL-Dried	Moisture	3842	PAL-LOOP	Brix
1498	PAL-98S	Condiment		Fruit Moisture			al products	DIIX
1439	PAL-39S	Hydrogen peroxide	4575	PAL-Dates Moisture	Moisture	4421	PAL-21S	Dextrin
1429	PAL-29S	Citric acid	Clinical,			4438	PAL-38S	Dimethylformamide
1430	PAL-30S	Acetic acid	4442	PAL-42S	Cesium chloride	4440	PAL-40S	Sodium hydroxide
1432	PAL-32S	Phosphoric acid	4453	PAL-53S	Copper sulfate (Concentration)	4423	PAL-23S	Glycerin (Low concentration)
1440	PAL-40S	Sodium hydroxide	4454	PAL-535	Copper sulfate (S.G.)	4424	PAL-24S	Glycerin (High concentration)
1464	PAL-64S	Sodium bicarbonate	4410	PAL-10S	Urine (S.G.)	4430	PAL-30S	Acetic acid
1465	PAL-65S	Sodium tartrate	4401	PAL-11S	Serum protein	4431	PAL-303	Formic acid
1470	PAL-70S	Potassium phosphate	4529		NEW Dog Urine (S.G.) / Cat Urine (S.G.)	4432	PAL-313	Phosphoric acid
1523	PAL-COFFEE		4510	PAL-DOGACAI	Dog Urine (S.G.)	4444	PAL-323	Lithium chloride
4532	PAL-COFFEE (TDS)	TDS	4510	PAL-DOG PAL-CAT	Cat Urine (S.G.)	4445	PAL-445 PAL-45S	Barium chloride
1533		Brix / TDS (Dual scale)	4511		Rabbit Urine (S.G.)	4446	PAL-455	Cobalt chloride
1000	(BX/TDS)	BIIX / TD3 (Dual scale)	Colostri		Nabbit Offile (3.G.)	4447	PAL-403 PAL-47S	Ferric chloride
1535	PAL-Tea	Tea	3805	PAL-Colostrum	Coloctrum	4448	PAL-473 PAL-48S	Strontium chloride
	d Vegetable G				Colostrum			
8847	PAL-ORANGE		Alcohol		Tabud alaah al (ast /100mal)	4449	PAL-49S	Potassium chloride Potassium bromide
8848	PAL-TOMATO		4433	PAL-33S	Ethyl alcohol (mL/100mL)	4450	PAL-50S	
8849	PAL-MAPLE		4434	PAL-34S	Ethyl alcohol (g/100g)	4451	PAL-51S	Sodium bromide
ugar	1712 14011 22	DIIX	4436	PAL-36S	Methyl alcohol	4452	PAL-52S	Potassium iodide
1412	PAL-12S	Dextran	4437	PAL-37S	Isopropyl alcohol (g/100g)	4453	PAL-53S	Copper sulfate (Concentration)
414	PAL-14S	Fructose	4530	PAL-131S	Isopropyl alcohol (mL/100mL)	4454	PAL-54S	Copper sulfate (S.G.)
415	PAL-15S	Glucose	4485	PAL-85S	Polyvinyl alcohol	4455	PAL-55S	Magnesium sulfate
416	PAL-16S	High Fructose Corn syrup (HFCS-42)		ceutical reage		4456	PAL-56S	Potassium sulfate
1417	PAL-17S	High Fructose Corn syrup (HFCS-55)	4412	PAL-12S	Dextran	4457	PAL-57S	Nickel sulfate
418	PAL-18S	Inverted suger	4413	PAL-13S	Creatine	4458	PAL-58S	Sodium sulfate
419	PAL-19S	Lactose	4423	PAL-23S	Glycerin (Low concentration)	4459	PAL-59S	Zinc sulfate
420	PAL-20S	Maltose	4424	PAL-24S	Glycerin (High concentration)	4460	PAL-60S	Silver nitrate
Vine, Bi		Waltose	4425	PAL-25S	Inulin	4461	PAL-61S	Sodium nitrate
1479	PAL-79S	T.A. 1990	4426	PAL-26S	Mannitol	4462	PAL-62S	Potassium carbonate
480	PAL-80S	T.A. 1971	4431	PAL-31S	Formic acid	4463	PAL-63S	Sodium carbonate
483	PAL-83S	KMW (or Babo)	4432	PAL-32S	Phosphoric acid	4464	PAL-64S	Sodium bicarbonate
484	PAL-84S	Baume	4451	PAL-51S	Sodium bromide	4467	PAL-67S	Potassium chromate
486	PAL-86S	Oe (Ger) / Brix (Dual scale)	4455	PAL-55S	Magnesium sulfate	4468	PAL-68S	Potassium dichromate
487	PAL-87S	Oe (Oechsle) / Brix (Dual scale)	4464	PAL-64S	Sodium bicarbonate	4469	PAL-69S	Sodium thiosulfate
540		Ethyl alcohol	4465	PAL-65S	Sodium tartrate	4470	PAL-70S	Potassium phosphate
541	PAL-Vodka	•	4466	PAL-66S	Potassium oxalate	4471	PAL-71S	Sodium molybdate
542		Ethyl alcohol	4468	PAL-68S	Potassium dichromate	4472	PAL-72S	Sodium tungstate
	PAL-Tequila	Ethyl alcohol	4470	PAL-70S	Potassium phosphate	Metal w		
1543		Ethyl alcohol	4472	PAL-72S	Sodium tungstate	4502	PAL-102S	Cutting oil
1544	PAL-Gin	Ethyl alcohol			, Heat Transfer, Industrial	4537	PAL-AntiRust	
545	PAL-Rum	Ethyl alcohol	4518	PAL-Urea	Urea	4536	PAL-Cleaner	
546	PAL-Brandy	Ethyl alcohol	4403	PAL-03S	Snow-melting agent (Sodium chloride)	4547	PAL-NMP	NEW N-methyl-2-pyrrolidone
1590	PAL-Plato	Plato (Sweet wort)	4441	PAL-41S	Snow-melting agent (Calcium chloride)	4558		NEW Hydrocarbon cleaner
	Seawater	Cadima ablanta (1900)	4443	PAL-43S	Snow-melting agent (Magnesium chloride)	Call C	Cleaner	contamination
1403	PAL-03S	Sodium chloride (g/100g)	4488	PAL-88S	Propylene glycol Freezing point of		il engineering	
1393	PAL-03CS	Sodium chloride (g/100g) / Freezing point of Sodium chloride (°C) (Dual scale)	4400	DAL OCC	Propylene glycol (°C)	4571	PAL-Soil	Gravimetric / Volumetric Soil moisture (Dual scale)
4506	PAL-106S	Sodium chloride (g/100mL)	4489	PAL-89S	Propylene glycol Freezing point of Propylene glycol (°F)			moisture (Duai scale)
1500	I AL-1003	Journal Chionae (g/ 100ml)			r ropyrene grycor (1)			

All ATAGO products are designed and manufactured in Japan.



ATAGO RUSSIA Ltd.

2-6-3 Shiba-koen, Minato-ku, Tokyo 105-0011, Japan TEL: 81-3-3431-1943 FAX: 81-3-3431-1945



ATAGO products comply with HACCP.GMP and GLP system standards.

http://www.atago.net/ overseas@atago.net ATAGO U.S.A., Inc. TEL: 1-425-637-2107 ATAGO INDIA Instruments Pvt. Ltd. CATAGO THAILAND Co.,Ltd, PATAGO BRASIL Ltda. ATAGO ITALIA s.r.l. ATAGO CHINA Guangzhou Co.,Ltd.

TEL: 66-21948727-9 TEL: 55 16 3913-8400 TEL: 7-812-777-96-96 ATAGO KAZAKHSTAN Ltd. TEL: 7-727-257-08-95

Copyright © 2019 ATAGO CO., LTD. All rights reserved. ENV.17 19081500PP Printed in Japan

"Pocket" Refractometers

_series







Brix 0.0 to 53.0%

PAL-3 Brix 0.0 to 93.0%

Cat.No.3870 Mode H[™] Technology Brix 0.0 to 93.0% Model

PAL-S Cat.No.3860 Mode S™ Brix 0.0 to 93.0% Technology Model

PAL-91S

Cat.No.4491 Ethylene glycol 0.0 to 90.0% (V/V)

Hydrogen peroxide 0.0 to 50.09

Pocket-Palm-Perform

























^{*} Specifications and appearance are subject to change without notice.

The Next Generation of Digital Refractometers

- ĪP65
- Extremely water resistant (IP65)
- Can be washed under running water
- Will float if accidentally dropped in water





- Ergonomically designed for one-handed operation
- The innovative design makes it easy to pour out and remove a sample, but difficult to spill the sample.



Automatic Temperature Compensation (ATC)



• Mode $S^{\text{\tiny{TM}}}$: Mode $S^{\text{\tiny{TM}}}$ improves repeatability of samples that cause inconsistent readings.



 Mode H[™]: Mode H[™] enables to measure the sample at high temperature in 2 seconds.

- Revolutionary new External Light interference (ELI)
 - When intense light penetrates the prism of a digital refractometer, the light waves interfere with the sensor, which may lead to inaccurate measurements. To ensure accurate measurement results, the PAL is programmed with the ELI function which displays the [nnn] warning message when intense direct light is detected. Forming a habit of shading the sample stage with your hand and re-pressing the START key (when the warning message from the ELI function is displayed) will ensure accurate measurement results each time.



- Measurement history (up to 100 items) can be read by touching a contactless IC card reader / writer connected to an Android smartphone or a personal computer.
- * The N-Mark is a trademark or registered trademark of NFC Forum, Inc. in the United States and in other countries.









Cat.No.3870







Low to medium

PAL-1 Cat.No.3810 Wide range PAL- 3 Cat.No.3830 Powered by Mode S™ PAL-S S Mode

Cat.No.3860

Standard accessory MAGICTM

Powered by Mode H™

Ethylene glycol (V/V) PAL-H PAL-91S

Cat.No.4491

PAL-39S

Cat.No.4439

Specifications

•									
	PAL-1 Cat.No.3810	PAL-3 Cat.No.3830	PAL-S Cat.No.3860	PAL-H Cat.No.3870	PAL-91S Cat.No.4491	PAL-39S Cat.No.4439			
Measurement range	Brix 0.0 to 53.0%	0.0 to Brix			E.G: 0.0 to 90.0 % (V/V) Freezing point: 0 to -50°C	Hydrogen peroxide 0.0 to 50.0%			
Resolution		Brix 0.1%		Brix 0.5%	E.G: 0.2 %(V/V) Freezing point: 1°C	Hydrogen peroxide 0.2%			
Measurement accuracy	Brix ±0.2%	Brix ±0.1%	Brix ±0.2%	Brix ±0.5%	E.G: ±0.4 % (Concentration of about 15%) Freezing point: ±1°C	Hydrogen peroxide ±0.6%			
Measurement temperature		10 to 35℃ (ATC)							
Ambient temperature				10 to 35℃					
Power supply	2×AAA Batteries								
International protection class	IP65 Water resistant								
Dimensions	5.5×3.1×10.9cm 100a								

Application examples



PAL commitment

A new ergonomic design for comfort and ease of use!

In pursuit of an "easy to use", "easy to operate" and ergonomic architecture of new instruments, ATAGO has achieved a "palmfitting" masterpiece as well as unit that is high in hygienic properties. By reducing the number of unnecessary assembly parts, we have reduced the risks of a germ reproductive environment. Through our efforts to produce a hygienic instrument to be used in any industry, these units are designed to be completely washable. The new PAL series has been approved by the HACCP, and are equipped with the new ELI feature, which ensures accurate measurements - even outdoors Requests from our customers worldwide are reflected in the development of the new PAL units.

Sample Stage

The SUS sample stage allows for the sample temperature to conform quickly and evenly to the prism temperature for accurate measurements.

START Key

Conveniently located for single hand operation.

NEW NFC

PAL series comes with Data Function with NFC technology.



Actua Size

"Pocket" Refractometers PA Series

EATAGO

(ZERO)

Made of highly durable optical glass to prevent scratching.

Liquid Crystal Display (LCD)

Digital measurement values are large and easy to read. Displays battery indicator and temperature.

ZERO Key

For Zero Setting, place water on the prism and press.

Strap Holder

Suitable for wrist straps or lanyards.

Measurement Method

Apply 2-3 drops on the prism



Press the START key.



Measurement value and prism 3 Measurement value and prism temperature are displayed in 3 seconds!

Optional

Part No.	Part Name.
RE-110010	Sucrose Solutions (for Brix confirmation) 10% (±0.03%)
RE-110020	Sucrose Solutions (for Brix confirmation) 20% (±0.03%)
RE-110030	Sucrose Solutions (for Brix confirmation) 30% (±0.03%)
RE-110040	Sucrose Solutions (for Brix confirmation)40% (±0.04%)
RE-110050	Sucrose Solutions (for Brix confirmation)50% (±0.05%)
RE-110060	Sucrose Solutions (for Brix confirmation)60% (±0.05%)
RE-39409	PAL-CASE
RE-39410	PAL-STRAP
RE-39446	MAGIC TM
RE-39412	Small Volume Sample Adapter for PAL
RE-39413	PAL Silicone Cover









◀ Sucrose Solutions

tom concentrations are available on request. Accuracy and prices will

Warranty period for these solutions is 6



■ MAGICTM This adaptor is used for a hot sample to cool it down quickly or to minir







Certification

In accordance with ISO Quality Management Systems, ATAGO can calibrate and certify your Digital Hand-Held "Pocket" Refractometer The following documents will be issued Distilled Water Saccharo (for a service 1st free): 3rd

- Calibration Certificate
- Traceability System Diagram
- Traceability Certificate